

# **SAFETY DATA SHEET**

Creation Date 13-Nov-2013 Revision Date 02-Apr-2024 Revision Number 5

# 1. Identification

Product Name Methyl methacrylate

Cat No. : A13030

CAS No 80-62-6 Synonyms MMA

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

#### Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill. MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Skin Corrosion/Irritation

Category 2
Serious Eye Damage/Eye Irritation

Skin Sensitization

Category 2
Category 2
Skin Sensitization

Category 1
Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system.

#### Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor Causes skin irritation

Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation



## **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

None identified

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl methacrylate	80-62-6	>95

## 4. First-aid measures

#### **Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Methyl methacrylate

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial

respiration. Get medical attention.

Ingestion Do NOT induce vomiting. Clean mouth with water. Get medical attention.

Most important symptoms and

effects

May cause allergic skin reaction. Difficulty in breathing. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness,

lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

Treat symptomatically **Notes to Physician** 

# Fire-fighting measures

**Suitable Extinguishing Media** Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical. Water mist may be used to cool closed

containers. Water mist may be used to cool closed containers.

**Unsuitable Extinguishing Media** No information available

8 °C / 46.4 °F **Flash Point** 

No information available Method -

**Autoignition Temperature** 430 °C / 806 °F

**Explosion Limits** 

Upper 12.5% Lower 2.1%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

## Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Up

Health **Flammability** Instability Physical hazards 2 3 N/A

# Accidental release measures

**Personal Precautions Environmental Precautions**  Remove all sources of ignition. Take precautionary measures against static discharges. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal, Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not let this chemical enter the

environment.

Methyl methacrylate

# 7. Handling and storage

Handling

Avoid contact with skin and eyes. Do not breathe mist/vapors/spray. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Refrigerator/flammables. Inhibitor levels should be maintained. Incompatible Materials. Acids. Bases. Amines. Halogens. Peroxides. Reducing Agent.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methyl methacrylate	TWA: 50 ppm	(Vacated) TWA: 100 ppm	IDLH: 1000 ppm	TWA: 50 ppm
	STEL: 100 ppm	(Vacated) TWA: 410 mg/m <sup>3</sup>	TWA: 100 ppm	STEL: 100 ppm
		TWA: 100 ppm	TWA: 410 mg/m <sup>3</sup>	
		TWA: 410 mg/m <sup>3</sup>	_	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting equipment.

**Personal Protective Equipment** 

**Eye/face Protection**Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended Filter type:** Organic gases and vapours filter. Type A. Brown. conforming to EN14387.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorStrong

Odor Threshold

pH

No information available
No information available

Melting Point/Range -48 °C / -54.4 °F

Boiling Point/Range 100 °C / 212 °F @ 760 mmHg

Flash Point 8 °C / 46.4 °F Evaporation Rate No information available

## Methyl methacrylate

Not applicable

Flammability (solid,gas)

Flammability or explosive limits

 Upper
 12.5%

 Lower
 2.1%

 Procedure
 40 mbar

 Vapor Pressure
 40 mbar @ 20 °C

 Vapor Density
 3.5 (Air = 1.0)

 Specific Gravity
 0.930

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature430 °C / 806 °FDecomposition TemperatureNo information availableViscosity0.6 mPa s at 20 °C

Molecular FormulaC5 H8 O2Molecular Weight100.12

# 10. Stability and reactivity

Reactive Hazard Yes

Stability Stable under normal conditions. Hazardous polymerization may occur upon depletion of

inhibitor.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products.

Incompatible Materials Acids, Bases, Amines, Halogens, Peroxides, Reducing Agent

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization may occur upon depletion of inhibitor.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

#### **Acute Toxicity**

# Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl methacrylate	LD50 8420 - 10000 mg/kg (Rat)	LD50 5000 - 7500 mg/kg (Rabbit)	LC50 = 29.8  mg/L  (Rat) 4  h

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

**Sensitization** May cause sensitization by skin contact

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl methacrylate	80-62-6	Not listed				

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental Effects

No information available.

Teratogenicity

No information available.

Methyl methacrylate

STOT - single exposure Respiratory system None known STOT - repeated exposure

No information available **Aspiration hazard** 

delayed

Symptoms / effects,both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is:. Harmful to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Component  Methyl methacrylate	Freshwater Algae EC50: = 170 mg/L, 96h (Pseudokirchneriella subcapitata)	LC50: 326.4 - 426.9 mg/L, 96h static (Poecilia reticulata) LC50: > 79 mg/L, 96h static (Oncorhynchus mykiss) LC50: > 79 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 153.9 - 341.8 mg/L, 96h static (Lepomis macrochirus) LC50: 170 - 206 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 125.5 - 190.7 mg/L, 96h static (Pimephales	Microtox Not listed	Water Flea EC50: = 69 mg/L, 48h (Daphnia magna)

**Persistence and Degradability** Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Methyl methacrylate	1.38

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl methacrylate - 80-62-6	U162	-

# 14. Transport information

## Methyl methacrylate

DOT

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3
Packing Group ||

TDG

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3
Packing Group ||

**IATA** 

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1247

Proper Shipping Name METHYL METHACRYLATE MONOMER, STABILIZED

Hazard Class 3
Packing Group ||

# 15. Regulatory information

## United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl methacrylate	80-62-6	X	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Not applicable

Substances & Mixtures, Under TSCA Section 6(h) (PBT)

TSCA 12(b) - Notices of Export Not applicable

#### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

	Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ī	Methyl methacrylate	80-62-6	X	-	201-297-1	X	X	Х	Х	Х	KE-25050

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Methyl methacrylate	80-62-6	>95	1.0 %	-

#### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

#### **CWA (Clean Water Act)**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Methyl methacrylate	X	1000 lb	-	-

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl methacrylate	X		-

**OSHA** - Occupational Safety and

Not applicable

Health Administration

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl methacrylate	1000 lb	<del>-</del>	1000 lb 454 kg

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl methacrylate	X	X	X	X	Х

#### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

This product does not contain any DHS chemicals.

Security

Other International Regulations

Mexico - Grade No information available

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl methacrylate	80-62-6	-	Use restricted. See item 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl methacrylate	80-62-6	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

#### Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - (2012/18/EC) - (2012/18/EC) - Qualifying Quantities		Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident	for Safety Report		
		Notification	Requirements		
Methyl methacrylate	80-62-6	Not applicable	Not applicable	Not applicable	Not applicable

4/	$\sim$ 1.1	1 6	
16	()ther	information	

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 13-Nov-2013

 Revision Date
 02-Apr-2024

 Print Date
 02-Apr-2024

**Revision Summary** New emergency telephone response service provider.

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**