

## SAFETY DATA SHEET

Creation Date 06-Apr-2010

Revision Date 14-May-2024

Revision Number 9

### 1. Identification

**Product Name** n-Butyllithium, 2.5M solution in hexanes

**Cat No. :** AC213350000; AC213350150; AC213350500; AC213351000;  
AC213351300; AC213358000

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

##### Company

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

##### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Substances/mixtures which, in contact with water, emit flammable gases	Category 1
Pyrophoric liquids	Category 1
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Liver, Central nervous system (CNS), Peripheral Nervous System (PNS).	
Aspiration Toxicity	Category 1

**Label Elements****Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Catches fire spontaneously if exposed to air

May be fatal if swallowed and enters airways

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness

Suspected of damaging fertility

May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Do not allow contact with air

Keep away from any possible contact with water, because of violent reaction and possible flash fire

Handle under inert gas. Protect from moisture

Keep cool

**Response**

Immediately call a POISON CENTER or doctor/physician

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Skin**

Wash contaminated clothing before reuse

IF ON SKIN: Immerse in cool water/wrap with wet bandages

Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

**Ingestion**

Do NOT induce vomiting

Rinse mouth

**Fire**In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction**Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store contents under inert gas  
Store in a dry place. Store in a closed container

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Toxic to aquatic life with long lasting effects

Reacts violently with water

WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

### 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Hexane	110-54-3	77
Butyl lithium	109-72-8	23

### 4. First-aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Most important symptoms and effects</b>	Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
<b>Notes to Physician</b>	Treat symptomatically

### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Water spray, fog or alcohol-resistant foam. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	DO NOT USE WATER, Carbon dioxide (CO <sub>2</sub> ), Foam
<b>Flash Point</b>	-21 °C / -5.8 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	No information available
<b>Explosion Limits</b>	No information available

**Upper** 7.40 vol %  
**Lower** 1.20 vol %  
**Sensitivity to Mechanical Impact** No information available  
**Sensitivity to Static Discharge** No information available

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Hazardous Combustion Products**

Butane. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA**

**Health** 3                      **Flammability** 4                      **Instability** 2                      **Physical hazards** W

**6. Accidental release measures**

**Personal Precautions** Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean Up** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

**7. Handling and storage**

**Handling** Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage.** Store under an inert atmosphere. Keep away from water or moist air. Keep refrigerated. Keep away from heat, sparks and flame. Flammables area. Protect from moisture. Keep container tightly closed. Incompatible Materials. Strong oxidizing agents. Halogens. Bases. Acids. Alcohols.

**8. Exposure controls / personal protection**

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m <sup>3</sup> TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup>	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>	TWA: 50 ppm

*Legend*

ACGIH - American Conference of Governmental Industrial Hygienists  
 OSHA - Occupational Safety and Health Administration  
 NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Yellow
<b>Odor</b>	Petroleum distillates
<b>Odor Threshold</b>	No information available
<b>pH</b>	Not applicable
<b>Melting Point/Range</b>	No data available
<b>Boiling Point/Range</b>	No information available
<b>Flash Point</b>	-21 °C / -5.8 °F
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
<b>Upper</b>	7.40 vol %
<b>Lower</b>	1.20 vol %
<b>Vapor Pressure</b>	160 mbar @ 20 °C
<b>Vapor Density</b>	No information available
<b>Specific Gravity</b>	0.690
<b>Solubility</b>	Reacts with water
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	No information available
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Molecular Formula</b>	C4 H9 Li
<b>Molecular Weight</b>	64.06

## 10. Stability and reactivity

**Reactive Hazard** Yes

**Stability** Pyrophoric: Spontaneously flammable in air. Reacts violently with water. Air sensitive. Moisture sensitive.

**Conditions to Avoid** Incompatible products. Heat, flames and sparks. Exposure to moist air or water. Exposure to air. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible Materials** Strong oxidizing agents, Halogens, Bases, Acids, Alcohols

**Hazardous Decomposition Products** Butane, Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing. Reacts violently with water.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

##### Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg ( Rat )	LD50 = 3000 mg/kg ( Rabbit )	LC50 = 48000 ppm ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** Causes burns by all exposure routes

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed
Butyl lithium	109-72-8	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** No information available

**Reproductive Effects** Experiments have shown reproductive toxicity effects on laboratory animals.

**Developmental Effects** Developmental effects have occurred in experimental animals.

**Teratogenicity** Teratogenic effects have occurred in experimental animals.

**STOT - single exposure** Respiratory system Central nervous system (CNS)

**STOT - repeated exposure** Liver Central nervous system (CNS) Peripheral Nervous System (PNS)

**Aspiration hazard** Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

## 12. Ecological information

### Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h

--	--	--	--

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment.

Component	log Pow
Hexane	4.11

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport information

**DOT**

**UN-No** UN3394  
**Proper Shipping Name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Technical Name** (N-BUTYLLITHIUM, HEXANE)  
**Hazard Class** 4.2  
**Subsidiary Hazard Class** 4.3  
**Packing Group** I

**TDG**

**UN-No** UN3394  
**Proper Shipping Name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Hazard Class** 4.2  
**Subsidiary Hazard Class** 4.3  
**Packing Group** I

**IATA**

**UN-No** UN3394  
**Proper Shipping Name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE, FORBIDDEN FOR IATA TRANSPORT  
**Hazard Class** 4.2  
**Subsidiary Hazard Class** 4.3  
**Packing Group** I

**IMDG/IMO**

**UN-No** UN3394  
**Proper Shipping Name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Hazard Class** 4.2  
**Subsidiary Hazard Class** 4.3  
**Packing Group** I

### 15. Regulatory information

**United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Hexane	110-54-3	X	ACTIVE	-
Butyl lithium	109-72-8	X	ACTIVE	-

**Legend:**

**TSCA** US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

**TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)** Not applicable

TSCA 12(b) - Notices of Export

Not applicable

**International Inventories**

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Hexane	110-54-3	X	-	203-777-6	X	X	X	X	X	KE-18626
Butyl lithium	109-72-8	X	-	203-698-7	X	X	X	X	X	KE-04320

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Hexane	110-54-3	77	1.0 %	-

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

Not applicable

**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Hexane	5000 lb	-	5000 lb 2270 kg

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Hexane	110-54-3	Male Reproductive	-	Developmental

**U.S. State Right-to-Know Regulations**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hexane	X	X	X	X	X
Butyl lithium	-	X	X	-	-

**U.S. Department of Transportation**



Reportable Quantity (RQ): Y  
 DOT Marine Pollutant Y  
 DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security** This product does not contain any DHS chemicals.

#### Other International Regulations

**Mexico - Grade** Serious risk, Grade 3

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	110-54-3	-	Use restricted. See item 75. (see link for restriction details)	-
Butyl lithium	109-72-8	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Hexane	110-54-3	Listed	Not applicable	Not applicable	Not applicable
Butyl lithium	109-72-8	Listed	Not applicable	Not applicable	Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

#### Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Hexane	110-54-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Butyl lithium	109-72-8	Not applicable	Not applicable	Not applicable	Not applicable

## 16. Other information

**Prepared By** Regulatory Affairs  
 Thermo Fisher Scientific  
 Email: EMSDS.RA@thermofisher.com

**Creation Date** 06-Apr-2010  
**Revision Date** 14-May-2024  
**Print Date** 14-May-2024  
**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**